

COUGAR 8520 CALCIUM SULFONATE COMPLEX GREASE NO.HB2

Cougar 8520 is an extreme pressure, water resistant, adhesive, high temperature calcium sulfonate complex grease especially formulated to provide high performance lubrication in a wide range of applications in industrial, marine and offshore applications operating under the most severe conditions of water, heat, dust and other pollutants.

Cougar 8520 is also suitable for use as a multi purpose grease in off road applications where contact with water is frequent.

FEATURES & BENEFITS

- Truly versatile can replace a wide range of conventional greases.
- Extraordinary water resistant, maintains consistency even with high levels of water contamination
- Adhesive - adheres to metal surfaces withstands pound out.
- Excellent anti-oxidation and corrosion performance
- Excellent thermal stability, reverts to original texture after high temperature exposure
- Excellent extreme pressure and anti-wear performance

SPECIFICATIONS

- ISO 6743-9: L-XBFHB2
- DIN 51 502: KP2R-25

TYPICAL CHARACTERISTICS

Grade CG	8520
NLGI Grade	2
Worked Penetration @ 77°F (25°C)	265 - 295
Colour	Red
Base Thickener	Calcium Sulfonate
Dropping Point °C	>300
Base Oil: Viscosity cSt @ 40°C	400
4 Ball Weld Load daN	500

This product information sheet was correct at the time of print, however, Cougar Lubrication Ltd operates a policy of continuous product development and as such reserves the right to change product names and specifications of the items described in this product information sheet at any time. For the latest information please contact your Cougar Supplier.



Rev. 03a07

FREEPHONE: 0800 163312

COUGAR LUBRICATION LTD
Registered in England No. 3358881