

COUGAR 8942 HAMMER AND CHISEL PASTE

Cougar 8942 Hammer & Chisel Paste has been especially designed to provide high performance lubrication of hydraulic hammers. It is manufactured from a Calcium Sulfonate complex thickener, containing more than 10% of copper and graphite solids which provide excellent high temperature, extreme pressure, and heavy load carrying capabilities.

Cougar 8942 Hammer & Chisel Paste also features the maximum 800 weld point score on the four ball EP (Extreme Pressure) test, one of the highest quality hydraulic hammer/breaker lubricants available.

Cougar 8942 is recommended for the greasing of the tool and bushings on hydraulic hammers and breakers to prevent wear and extend life of the tool and meets all OEM requirements for hydraulic hammer and hydraulic breaker lubrication

FEATURES & BENEFITS

- Fortified with copper and graphite
- Excellent load and shock resistance properties. Weld point score of 800
- Calcium Sulfonate Complex thickener
- Heavy duty ISO 460 base oil.
- Inherently adhesive.

TYPICAL CHARACTERISTICS

NLGI Grade	2
Colour	Copper / Grey
Thickener Type	Calcium Sulfonate Complex
Penetration Worked D 217	265 - 290
Dropping Point, min D 2265	298°C
4-Ball EP, weld point D 2596	800 kg
4-Ball Wear, Scar Dia, mm D 2266	0.39
Corrosion Prevention D 1743	PASS
Solids, Graphite & Copper	10 %
Base Oil Viscosity @ 40°C, cSt	460
Viscosity Index	95
Dry Film Lubrication	982 + °C



product information sheet was correct at the time of print, however, Cougar Lubricants International Ltd operates a policy to change product names and specifications of the items described in this product information sheet at any time. For

PHONE: 0203 011 5575

WWW.COUGAR-LUBRICANTSINT.COM

COUGAR LUBRICANTS INTERNATIONAL LTD

Registered in England No 08401804